

# Versilon™ G-FDA Hose

## High Temperature Suction and Discharge Rubber Hose

Versilon G-FDA is built for higher temperatures and more chemically demanding applications. It boasts our highest temperature rating for any non-fluoropolymer lined rubber covered hose.

The non-PVC, non-butyl, all EPDM liner is designed to reduce the risk of taste and odor adulteration of food.

A robust dual-helix wire reinforcement allows the EPDM liner to withstand full vacuum, making it the best EPDM lined hose for suction and discharge service.

### Features and Benefits

- Sanitary suction and discharge hose
- White EPDM liner
- EPDM cover and reinforcements designed to withstand rough handling and high temperatures
- Full vacuum rating
- Food oil and ozone resistant
- Custom laylines available
- Specially designed to handle oil based materials
- Designed to reduce risk of taste and odor adulteration of food

### Typical Applications

- Cosmetics
- High purity water
- Bulk food transfer
- Beverage
- Dairy
- CIP applications

### Regulatory Compliance

- Compliant with FDA 21CFR 177.2600
- USDA
- 3-A Sanitary Standard 62-02

## G-FDA Hose Specifications

Part Number	Inside Diameter		Outside Diameter		Maximum Working Pressure*		Minimum Burst Pressure		Minimum Bend Radius**		Vacuum Hg		Weight	
	(in)	(mm)	(in)	(mm)	(psi)	(MPa)	(psi)	(MPa)	(in)	(mm)	(in)	(mm)	(lb/ft)	(kg/m)
GFDA-0500	0.50	12.7	0.98	24.9	150	1.03	600	4.14	2.50	63.5	29.9	760	0.30	0.45
GFDA-0750	0.75	19.1	1.27	32.3	150	1.03	600	4.14	3.75	95.3	29.9	760	0.44	0.65
GFDA-1000	1.00	25.4	1.50	38.1	150	1.03	600	4.14	4.00	101.6	29.9	760	0.57	0.85
GFDA-1500	1.50	38.1	2.09	53.1	150	1.03	600	4.14	5.00	127.0	29.9	760	0.91	1.35
GFDA-2000	2.00	50.8	2.63	66.8	150	1.03	600	4.14	6.00	152.4	29.9	760	1.30	1.93
GFDA-2500	2.50	63.5	3.17	80.5	150	1.03	600	4.14	7.00	177.8	29.9	760	1.74	2.59
GFDA-3000	3.00	76.2	3.72	94.5	150	1.03	600	4.14	8.00	203.2	29.9	760	2.42	3.60
GFDA-4000	4.00	101.6	4.78	121.4	150	1.03	600	4.14	11.00	279.4	29.9	760	3.22	4.79

NOTE: Weights and outside diameter dimensions are nominal. Data given is for hose only. End fitting vs. hose pressure limitations must be considered and the lower of the two ratings must be used on assemblies.

\* Based on ambient condition on exterior of hose. Elevated temperatures and characteristics of medium being transferred can affect working pressures and burst pressures.

\*\* Measured on the inner surface of the curved portion. Data is based on static applications. For dynamic or cyclic applications, consult factory.

## Construction

Inner Tube:	Seamless white EPDM																
Cover:	EPDM																
Reinforcement:	Two fabric spirals with dual helix wire																
Color:	Gray with a white layline in blue lettering																
Temperature Rating:	-40°F to +300°F -40°C to +149°C																
Maximum Length:	<table border="1"> <tr> <td>1/2"</td> <td>60'</td> <td>2"</td> <td>60'</td> </tr> <tr> <td>3/4"</td> <td>60'</td> <td>2-1/2"</td> <td>50'</td> </tr> <tr> <td>1"</td> <td>60'</td> <td>3"</td> <td>60'</td> </tr> <tr> <td>1-1/2"</td> <td>60'</td> <td>4"</td> <td>60'</td> </tr> </table>	1/2"	60'	2"	60'	3/4"	60'	2-1/2"	50'	1"	60'	3"	60'	1-1/2"	60'	4"	60'
1/2"	60'	2"	60'														
3/4"	60'	2-1/2"	50'														
1"	60'	3"	60'														
1-1/2"	60'	4"	60'														

## Fitting Options

### Versilon Crimp Style Fittings

- Over 40 styles of stocked crimp-style fittings in a wide range of materials
- Standard: 316L stainless steel (wetted surfaces)

**Limited Warranty:** For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



Saint-Gobain Performance Plastics  
210 Harmony Road  
Mickleton, NJ 08056  
1-800-435-3992

www.processsystems.saint-gobain.com



NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

Versilon™ is a trademark of Saint-Gobain Performance Plastics.